

Exterior Nails


Roofing Nail — Annular Ring Shank

Features:

- Large, flat head provides extra bearing surface to firmly secure roofing material
- Annular ring shank increases withdrawal resistance to provide a secure attachment to wood members and plywood roof decks
- Longer lengths ideal for installing curved Spanish roof tiles and thicker slate
- Aluminum nails also available with a screw shank; call Simpson Strong-Tie for details (800) 999-5099

Installation Tips:


- For slate roofs, determine the correct nail length by doubling the slate thickness and adding one inch



Type 316 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
—	¾	10	0.131	¾	0.375	281	T7510ARN1	T7510ARN5	T7510ARNB
2d	1	10	0.131	¾	0.375	212	T210ARN1	T210ARN5	T210ARNB
3d	1¼	10	0.131	¾	0.375	166	T310ARN1	T310ARN5	T310ARNB
3d	1¼	11	0.120	1½/32	0.344	199	T311ARN1	—	T311ARNB
4d	1½	10	0.131	¾	0.375	139	T410ARN1	T410ARN5	T410ARNB
4d	1½	11	0.120	1½/32	0.344	170	T411ARN1	T411ARN5	T411ARNB
5d	1¾	10	0.131	¾	0.375	126	T510ARN1	T510ARN5	T510ARNB
6d	2	10	0.131	¾	0.375	105	T610ARN1	T610ARN5	T610ARNB
8d	2½	10	0.131	¾	0.375	91	T810ARN1*	T810ARN5*	T810ARNB*
10d	3	10	0.131	¾	0.375	78	T1010ARN1*	T1010ARN5*	T1010ARNB*

*Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.



Type 304 Stainless Steel

Penny Size	Length (in.)	Gauge	Shank Diameter (in.)	Head Diameter (in.)		Approx. Count per lb.	1 lb. Model No.	5 lb. Model No.	25 lb. Bucket Model No.
—	¾	10	0.131	¾	0.375	281	S7510ARN1	S7510ARN5	S7510ARNB
2d	1	10	0.131	¾	0.375	212	S210ARN1	S210ARN5	S210ARNB
3d	1¼	10	0.131	¾	0.375	166	S310ARN1	S310ARN5	S310ARNB
3d	1¼	11	0.120	¾	0.375	199	—	S311ARN5	S311ARNB
4d	1½	10	0.131	¾	0.375	139	S410ARN1	S410ARN5	S410ARNB
4d	1½	11	0.120	¾	0.375	170	S411ARN1	S411ARN5	S411ARNB
5d	1¾	10	0.131	¾	0.375	126	S510ARN1	S510ARN5	S510ARNB
5d	1¾	11	0.120	¾	0.375	149	—	S511ARN5	S511ARNB
6d	2	10	0.131	¾	0.375	105	S610ARN1	S610ARN5	S610ARNB
6d	2	11	0.120	¾	0.375	136	S611ARN1	—	S611ARNB
8d	2½	10	0.131	¾	0.375	91	S810ARN1*	S810ARN5*	S810ARNB*
10d	3	10	0.131	¾	0.375	78	S1010ARN1*	S1010ARN5*	S1010ARNB*

*Complies with ASTM F1667 specifications for roof-sheathing ring-shank nails.

These products are subject to quantities on hand, or may require special-order, minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.