

Metal Screws

Self-Drilling Fiber-Cement Screw

Common Applications:


- Fasten fiber-cement products through furring strips to steel studs

Features:

- Wafer head, square drive, self-countersinking nibs under the head.
- Threaded to within $\frac{5}{16}$ " of top of head.
- #3 drill point.
- #2 square drive (replacement bit model BIT2S-2-R2)
- Type 410 stainless steel is coated for additional corrosion protection.
- Type 410 stainless steel can be hardened through heat treatment, giving it the ability to drill through metal. It does not offer the same level of corrosion resistance of either Type 316 or Type 305 stainless steel.
- **Warning:** Hardened stainless-steel fasteners should not be used with steel framing in environments with high humidity, condensation or other moisture that will be present at the dissimilar-metal interface.

For more information regarding driver bits for Simpson Strong-Tie fasteners, see p. 129.

For more information on drilling thickness capacities and drill speed recommendations, see pp. 26–27.



Type 410 Stainless Steel*

Size	Length (in.)	Max. Grip Length (in.)	Threads per Inch	Head Diameter (in.)	Carton Quantity	Model No.
#8	1 $\frac{5}{8}$	1.151	18	0.390	100	F08T162WDC
#8	1 $\frac{5}{8}$	1.151	18	0.390	1,000	F08T162WDM
#8	1 $\frac{5}{8}$	1.151	18	0.390	3,000	F08T162WDB
#8	2 $\frac{1}{4}$	1.801	18	0.390	100	F08T225WDC
#8	2 $\frac{1}{4}$	1.801	18	0.390	1,000	F08T225WDM
#8	2 $\frac{1}{4}$	1.801	18	0.390	2,500	F08T225WDB

*These products are subject to quantities on hand or may require special ordering and are subject to minimum order quantities and longer lead times. Call Simpson Strong-Tie for details (800) 999-5099.

1. Grip length includes side member, steel thickness, air gap (if any) and allowance for three threads protruding through the steel.